

VALVE ELECTRONIC **CV2016**

GENERAL POST OFFICE: E-IN-C (S)

Specification: GPO/CV 2016/Issue 1A Dated: October 1963. To be read in conjunction with K 1001	<u>SECURITY</u>	
	<u>Specification</u> Unclassified	<u>Valve</u> Unclassified

—————> indicates a change

<p><u>TYPE OF VALVE:</u> Double Triode</p> <p><u>CATHODE:</u> Indirectly heated</p> <p><u>ENVELOPE:</u> Glass, unmetallised</p> <p><u>PROTOTYPE</u> CV 455</p>	<p style="text-align: center;"><u>MARKING</u></p> <p style="text-align: center;">See K1001/4.1</p> <p style="text-align: center;"><u>PACKING</u></p> <p style="text-align: center;">See K 1005</p>
<p style="text-align: center;"><u>BASE</u></p> <p style="text-align: center;">B9A/B</p>	
<p>→ This Valve is a CV 4024 with tags welded to the pins and fitted with SRBP disc, in accordance with P.O. drawing CD 733 intended for mounting in a B9A Solder-in Valveholder.</p> <p style="text-align: center;">(See Outline Drawing on page 2)</p>	

(204332)

CV2016

OUTLINE DRAWING

