

Sharp-Cutoff Pentode

7-PIN MINIATURE TYPE

The 3DK6 is the same as the 6DK6 except for the following items:

Heater Characteristics and Ratings:

Current.	0.600 ± 0.040	amp
Voltage (AC or DC) at heater amperes = 0.600.	3.15	volts
Warm-up time (Average)	11	sec
Peak heater-cathode voltage:		
Heater negative with respect to cathode	300 ^a max.	volts
Heater positive with respect to cathode	200 ^b max.	volts

3DT6A

Sharp-Cutoff Pentode

With Two Independent Control Grids

7-PIN MINIATURE TYPE

The 3DT6A is the same as the 6DT6A except for the following items:

Heater Characteristics and Ratings:

Current.	0.600 ± 0.040	amp
Voltage (AC or DC) at heater amperes = 0.600.	3.15	volts
Warm-up time (Average)	11	sec

^a The dc component must not exceed 200 volts.

^b The dc component must not exceed 100 volts.



3DZ4

Medium-Mu Triode

7-PIN MINIATURE TYPE

The 3DZ4 is the same as the 6DZ4 except for the following items:

Heater Characteristics and Ratings:

Current	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450	3.2	volts
Warm-up time (Average)	11	sec
Peak heater-cathode voltage:		
Heater negative with respect to cathode	180 max.	volts
Heater positive with respect to cathode	180 ^b max.	sec

3EA5

Sharp-Cutoff Tetrode

7-PIN MINIATURE TYPE

The 3EA5 is the same as the 6EA5 except for the following items:

Heater Characteristics and Ratings:

Current	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450	2.9	volts
Warm-up time (Average)	11	sec

3EH7

Semiremote-Cutoff Pentode

9-PIN MINIATURE TYPE

The 3EH7 is the same as the 6EH7 except for the following items:

Heater Characteristics and Ratings:

Current	0.600 ± 0.040	amp
Voltage (AC or DC) at heater amperes = 0.600	3.4	volts

^b The dc component must not exceed 100 volts.

