

TUBE TYPE 14K7

The 14K7 is a triode-hexode converter, the hexode section having remote cut-off characteristics.

PHYSICAL SPECIFICATIONS

Cathode	Coated unipotential
Base	E8-30
Bulb	Glass
Maximum overall length	2-3/8" (60mm)
Maximum seated height	2-1/16" (53mm)
Maximum diameter	7/8" (22mm)
Mounting position	Any

BASING CONNECTIONS 8GY

Pin 1	Heater	Pin 5	Hexode Grids No.2 & No.4
Pin 2	Hexode Plate	Pin 6	Hexode Grid No.1
Pin 3	Triode Plate	Pin 7	Cathode
Pin 4	Hexode Grid No.3, Triode Grid	Pin 8	Heater

GENERAL ELECTRICAL DATA

Heater voltage	14	volts
Heater current	0.1	amps

CHARACTERISTICS

Hexode Section

Plate voltage	200	volts
Grids No.2 & No.4 voltage	85	volts
Plate current	3.0	ma
Grids No.2 & No.4 current	3.0	ma
Grid No.1 voltage	-2.0	volts
Conversion transconductance	750	µmhos
Plate resistance	>1.0	megohms
Grid No.1 bias for conversion transconductance of 7.5 µmhos	-27.5	volts

Triode Section

Plate voltage	100	volts
Plate current	10	ma
Grid voltage	0	volts
Transconductance	2,800	µmhos
Amplification Factor	22	

ELECTRODE CAPACITANCES

Hexode Grid No. 1 to Triode Grid	<0.35	μμF
Hexode Plate to Triode Grid	<0.2	μμF

Hexode Section

Input	3.8	μμF
Output	9.2	μμF
Plate to Grid No. 1	<0.1	μμF
Grid No. 1 to heater	<0.15	μμF

Triode Section

Input	5.5	μμF
Output	2.3	μμF
Plate to Grid	1.2	μμF

MAXIMUM RATINGS (Design centre values.)Hexode Section

Plate supply voltage	550	volts
Plate voltage	250	volts
Plate dissipation	1.5	watts
Grids No.2 & No.4 supply voltage	550	volts
Grids No.2 & No.4 voltage (Plate current = 3ma)	125	volts
(Plate current < 1ma)	250	volts
Grids No.2 & No.4 dissipation	0.3	watts
Cathode current	7	ma
Grid No.1 circuit resistance	3	megohms
Grid No.3 circuit resistance	3	megohms
Voltage between heater and cathode	150	volts
External resistance between heater and cathode	20,000	ohms.

Triode Section

Plate supply voltage	550	volts
Plate voltage	175	volts
Plate dissipation	0.8	watts
Cathode current	6.0	ma
Grid circuit resistance	3	megohms.







